

# AD125A

## AccuDrop™ Drop Tester

**L.A.B Equipment Introduces a Super Edge in Drop Tester!**

<b>Machine Type</b>	AccuDrop™ Drop Tester System
<b>Payload Capacity</b>	132 lbs (60 kg)
<b>Applicable Standards</b>	ASTM, TAPPI, ISO, JIS and ISTA
<b>Drive System</b>	Precision Servo Ball Screw Drive System
<b>Drop Height</b>	12"-72" (300 mm x 1820 mm)
<b>Package Size</b>	32" (813 mm) deep, unlimited height or width
<b>Impact Zone</b>	ASTM-approved, 30" wide by 32" deep (762 mm x 813 mm)
<b>Utility Requirement</b>	120V/1Ø/50-60 Hz, 10 Amp, 90 psi, 2 cfm filtered, dry shop air



### **Other Descriptive Features:**

- Adjustable Air Control valve and dual unit flow gauge to regulate and display air pressure
- Adjustable limit switches for upper and lower drop height stops
- Hand-held Control Pendant:
  - Positions the drop head to the desired drop height
  - Release the Drop Arm
  - Resets the Drop Arm
  - All Operator Controls in an Ergonomic Controller (no Foot Switch)
- Digital counter tracks the number of drops performed for Usability and Maintenance monitoring
- Versatile Corner and Edge Holding Device
- Sonar alert initiated with release of Drop Arm
- Complies with ISTA, ASTM, ISO and other internationally and industrially recognized standards.



OUR EQUIPMENT. YOUR SUCCESS.

**L.A.B. Equipment, Inc.**

1091 E. Green Street, Franklin Park, Illinois 60130, USA  
P: 630.595.4288 • F: 630.595.5196

E-mail: [sales@labequipment.com](mailto:sales@labequipment.com) Web: [www.labequipment.com](http://www.labequipment.com)