

AD160

AccuDrop™ Drop Tester

The Ultimate Drop Tester

Machine Type	AccuDrop™ Drop Tester System
Maximum Payload Capacity	160 lbs (73 kg)
Maximum Package Size	24" (600 mm) deep, unlimited width and height
Drop Operation	Solenoid Foot Switch
Drop Height	12"-84" (300 mm x 2134 mm), adjusted via Electric Hoist Additional drop height available, contact Sales
Maximum Package Size	36" deep, unlimited height or width
Impact Surface	ASTM-approved, 30" wide by 45" deep (762 mm x 1143 mm)
Standard Utility Requirement	110V/1Ø/60Hz, 50 psi, 2 cfm filtered, dry shop air

Model AD160



Other Descriptive Features:

- Package Holding Fixture (PHF) holds package in correct orientation prior to drop. Adjustable goose-neck arm with contoured fixture may be easily removed or swung out of the way when not in use.
- Hand held control pendant returns the drop head to the desired drop height.
- Drop controls reside in a foot actuated control station.
- Package support arm is reset to the "drop ready" mode with the foot switch.
- Dual reading indicator scale allows drop height to be read from both above or below drop head housing.
- Complies with ISTA, ASTM, ISO and other internationally and industrially recognized standards.



OUR EQUIPMENT. YOUR SUCCESS.

L.A.B. Equipment, Inc.

1091 E. Green Street, Franklin Park, Illinois 60130, USA
P: 630.595.4288 ▪ F: 630.595.5196

E-mail: sales@labequipment.com Web: www.labequipment.com